

Pursuant to 37 C.F.R. §1.121(b), please amend the specification by replacing the paragraph at page 3, line 6 with the following paragraph in clean form:

The invention relates to displaying transparent images. In one embodiment, a method includes generating a mask of the transparent image, where each pixel of the mask that corresponds to a transparent pixel of the image is set to a first predetermined color, and all other pixels are set to a second predetermined color. The image itself is transformed so that each pixel thereof that is transparent is set to the second color as well. In one embodiment, the mask generation and image transformation are performed in a first stage, such that the mask is cached.

In the Claims:

Pursuant to 37 C.F.R. §1.121(c), please amend the claims as shown in the following clean version of the entire set of pending claims:

1. (Amended) A computer-implemented method for displaying a transparent image at a location on a display, the transparent image having a plurality of pixels, some of which are transparent, the method comprising:

generating a mask of the transparent image having a plurality of pixels corresponding to the plurality of pixels of the transparent image, such that each pixel of the mask that corresponds to a transparent pixel of the image is set to a first predetermined color, and every other pixel of the mask is set to a second predetermined color;

transforming the transparent image such that each pixel thereof that is transparent is set to the second predetermined color;

copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display; and,

copying the transparent image as has been transformed to the location on the display such
that only pixels of the image other than those set to the second predetermined color are copied to
corresponding pixels of the display.

2. (Unchanged) The method of claim 1, wherein the method is further for displaying the
transparent image at a second location on the display, such that the method further comprises:

copying the mask to the second location on the display such that only pixels of the mask
that have been set to the second predetermined color are copied to corresponding pixels of the
display; and,

copying the transparent image as has been transformed to the second location on the
display such that only pixels of the mask other than those set to the second predetermined color
are copied to corresponding pixels of the display.

3. (Unchanged) The method of claim 2, wherein the method is further for displaying the
transparent image at a third location on the display, such that the method further comprises:

copying the mask to the third location on the display such that only pixels of the mask
that have been set to the second predetermined color are copied to corresponding pixels of the
display; and,

copying the transparent image as has been transformed to the third location on the display
such that only pixels of the mask other than those set to the second predetermined color are
copied to corresponding pixels of the display.

4. (Unchanged) The method of claim 1, wherein generating the mask comprises, for an
object for the mask having a background color, a text color, and a monochrome bitmap:

setting the background color of the object to the first predetermined color;

setting the text color of the object to the second predetermined color; and,

block-transferring the image to the monochrome bitmap.

5. (Unchanged) The method of claim 1, wherein transforming the transparent image comprises block-transferring an inverse of the mask onto the image with a predetermined and operation, where the transparent image also has an object therefor having a background color, a text color, and a bitmap.

6. (Unchanged) The method of claim 1, wherein copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display comprises:

for an object for the location on the display having a background color, a text color, and a bitmap,

setting the background color to the first predetermined color and the text color to the second predetermined color; and,

block-transferring an object for the mask to the object for the location on the display with a predetermined and operation.

7. (Unchanged) The method of claim 1, wherein copying the transparent image as has been transformed to the location on the display such that only pixels of the mask other than those set to the second predetermined color are copied to corresponding pixels of the display comprises block-transferring an object for the transparent image to an object for the location on the display with a predetermined or operation.

8. (Unchanged) The method of claim 1, wherein the second predetermined color comprises a logical zero color referred to as black.

9. (Unchanged) The method of claim 1, wherein the first predetermined color comprises a logical one color referred to as white.

10. (Unchanged) The method of claim 1, further comprising caching the mask of the transparent image.

11. (Unchanged) The method of claim 1, wherein the image comprises one of a plurality of frames of an animation.

12. (Unchanged) The method of claim 1, wherein the transparent image as displayed at the location on the display is shrunk and/or stretched.

13. (Amended) A machine-readable medium having instructions stored thereon for execution by a processor to perform a method for displaying a transparent image at at least one location on a display, the transparent image having a plurality of pixels, some of which are transparent, the method comprising:

performing once a first stage comprising:

generating a mask of the transparent image having a plurality of pixels corresponding to the plurality of pixels of the transparent image, such that each pixel of the mask that corresponds to a transparent pixel of the image is set to a first predetermined color, and every other pixel of the mask is set to a second predetermined color;

transforming the transparent image such that each pixel thereof that is transparent is set to the second predetermined color; and,

performing for each location at which the image is to be displayed a second stage comprising:

copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display; and,

cancel
copying the transparent image as has been transformed to the location on the display such that only pixels of the mask other than those set to the second predetermined color are copied to corresponding pixels of the display.

14. (Unchanged) The medium of claim 13, wherein generating the mask comprises, for an object for the mask having a background color, a text color, and a monochrome bitmap:

setting the background color of the object to the first predetermined color;

setting the text color of the object to the second predetermined color; and,

block-transferring the image to the monochrome bitmap.

15. (Unchanged) The medium of claim 13, wherein transforming the transparent image comprises block-transferring an inverse of the mask onto the image with a predetermined and operation, where the transparent image also has an object therefor having a background color, a text color, and a bitmap.

cancel
16. (Unchanged) The medium of claim 13, wherein copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display comprises:

for an object for the location on the display having a background color, a text color, and a bitmap, setting the background color to the first predetermined color and the text color to the second predetermined color; and,

block-transferring an object for the mask to the object for the location on the display with a predetermined and operation.

17. (Unchanged) The method of claim 13, wherein copying the transparent image as has been transformed to the location on the display such that only pixels of the mask other than those set to the second predetermined color are copied to corresponding pixels of the display comprises

block-transferring an object for the transparent image to an object for the location on the display with a predetermined operation.

NE. 18. (Unchanged) The medium of claim 13, wherein performing once the first stage further comprises caching the mask of the transparent image.

19. (Amended) A computer-implemented method for displaying a transparent image at a location on a display, the transparent image having a plurality of pixels, some of which are transparent, the method comprising:

generating a mask of the transparent image having a plurality of pixels corresponding to the plurality of pixels of the transparent image, such that each pixel of the mask that corresponds to a transparent pixel of one of the transparent image and a pattern image is set to a first predetermined color, and every other pixel of the mask is set to a second predetermined color;

transforming the transparent image such that each pixel thereof that is transparent is set to the second predetermined color;

copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display; and,

copying the transparent image as has been transformed to the location on the display such that only pixels of the mask other than those set to the second predetermined color are copied to corresponding pixels of the display.

NE. 20. (Unchanged) The method of claim 19, wherein the pattern image comprises a dithering pattern image.

21. (Unchanged) The method of claim 19, wherein the pattern image comprises a dithering pattern image used in alpha blending.

22. (Unchanged) A computer comprising:

a display;

a class library having a function designed to display a transparent image on the display, the function caching a mask for the image and a transformation of the image used for displaying the image, such that subsequent calls to the function for displaying the image omit regenerating the mask and retransforming the image; and,

an application program designed to call the function of the class library a plurality of times to display the image at different locations on the display.

23. (Unchanged) The computer of claim 22, wherein the class library comprises at least one computer program executed by a processor of the computer from a computer-readable medium thereof.

24. (Unchanged) The computer of claim 22, wherein the function further generates the mask such that the mask has a plurality of pixels corresponding to the plurality of pixels of the transparent image, such that each pixel of the mask that corresponds to a transparent pixel of the image is set to a first predetermined color, and every other pixel of the mask is set to a second predetermined color.

25. (Unchanged) The computer of claim 24, wherein the function further transforms the transparent image such that each pixel thereof that is transparent is set to the second predetermined color.

26. (Unchanged) The computer of claim 24, wherein the function is to display the image by copying the mask to the location on the display such that only pixels of the mask that have been set to the second predetermined color are copied to corresponding pixels of the display, and by copying the transformation of the image to the location on the display such that only pixels of the